

MOTORIZED AUTO DRAIN VALVE

Model - ZERO AIR LOSS (ESSAD-161)



CONCEPT ESSAD-161 is Designed to Remove Condensate from Compressed Air Systems. Most Suitable for installation, Moisture Separator etc. Valve has facility to drain manually on power failure.

Specifications :

Timer

- Supply Voltage : 240 VAC (180-260 VAC) 50 Hz (Other on request)
- Operating Temp. : 70°C (Maximum)
- Enclosure Housing : Aluminum
- Connection : DIN 43650 A with Power Indication
- Indications : LED (Red)- Power On

Valve

- Type : 2 Way Direct Acting
- In/Out Ports : 1/2" BSP (F)
- Working Pressure : 16 Kg/cm²
- Valve Body : Bar Stock Aluminium
- Orifice : 2.5 mm



Model - ESSAD-161

Benefits

- Energy Efficient
- High Reliability
- Low Maintenance
- Reliable all digital electronic circuit
- Power & Drain status indicator

Motorised Auto Drain Valve - ESSAD - 161

Model	Orifice	MWP	Connection Size	Features	Application	Remarks
ESSAD-161	2.5 mm	16 Kg/cm ²	1/2" BSP (F)	Test Switch, Inbuilt Strainer	Big Size Receivers	High Performance, Valve for Air Receiver



CONCEPT TECHNOSTRUCTURES

Horizon Tower, 504, 5th Floor, J.L.N. Marg, Jaipur - 302017, India
M. No.: +91- 8875009534, 9799917442
Tel. No.+91- 0141-4981363
Email : sales@conceptgroups.com / conceptsalesjpr@conceptgroups.com
conceptjpr@conceptgroups.com
Website : www.conceptgroups.com

Certificate Number:
114629/A/0001/UK/En
ISO 9001:2015



CONCEPT
ADV - R-01